



## art. 8059 IPER-LORD/AR

<b>Mod</b>	AR	<b>Installation</b>	Indoor and outdoor floodlight
<b>Material</b>	Die cast aluminium body, painted with polyester coated anticorrosion powder silver color, tempered transparent glass mm 5 thickness, silicon gasket	<b>Insulation class</b>	Class I
<b>Protection index</b>	IP65	<b>Impact degree</b>	IK08
<b>Ambient temperature (Ta)</b>	-25 / +45 °C	<b>Optics</b>	Matt satin symmetric aluminium reflector
<b>Power supply</b>	220-240V 50/60Hz	<b>Flicker</b>	Low flicker
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1:2015	<b>Warranty</b>	7 Years
<b>Luminous flux maintenance</b>	L80-B20 (50.000h) - L80-B50 (75.000h)	<b>Photobiological safety class</b>	IEC 62471: Exempt group
<b>Beam angle</b>	55°		

### CODE

<b>Art.</b>	+	<b>Mod.</b>	+	<b>°K</b>	+	<b>W-tot.</b>	+	<b>Opt.</b>
8059		AR		3 = 3000°K		120 = 1200W		GR = standard
				4 = 4000°K		135 = 1350W		GL = driver on-board (38 Kg)
				5 = 5000°K				GM = 1-10 V
				6 = 6500°K				GD = dali
								GS = sanded glass
								GI = shatterproof glass

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	D	Kg	Lamp	Sost.
1200	4000	199871	151063	720	105	680	400	28,5	18 led	2000W JM/SAP
1350	4000	222409	168029	720	105	680	400	28,5	18 led	2000W JM/SAP
BOX	A	B	C	Kg						
	470	210	200	11,0						

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

• 3000K = -5,28% lm • 4000K = standard • 5000K = +0,90% lm • 6500K = +3.0% lm

