



art. 8059 IPER-LORD/PM

Mod	PM	Installation	Indoor and outdoor floodlight
Material	Silver extruded aluminium oxydate body, zinc-coated bracket, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP65	Impact degree	IK08
Color rendering index	> 80	Ambient temperature (Ta)	-25 / +45 °C
Optics	Matt satin symmetric aluminium reflector	Power supply	220-240V 50/60Hz
Flicker	Low flicker	Incandescent wire resistance	850°
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 years
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	90°	RAL	9006

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
8059		PM		3 = 3000°K		120 = 1200W		GR = standard
				4 = 4000°K		135 = 1350W		GL = driver on-board (38 Kg)
				5 = 5000°K				GM = 1-10 V
				6 = 6500°K				GD = dali
								GS = sanded glass
								GV = shatterproof glass

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	D	Kg	Lamp	Sost.
1200	4000	199871	141621	720	105	680	400	28,5	18 led	2000W JM/SAP
1350	4000	222409	157527	720	105	680	400	28,5	18 led	2000W JM/SAP
BOX	A	B	C	Kg						
	470	210	200	11,0						

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

