



art. 8036 LORD 2/R

Mod	AR	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder silver color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP66	Impact degree	IK08
Ambient temperature (Ta)	-25 / +45 °C	Optics	45° asymmetric beam matt satin aluminium reflector.
Power supply	220-240V 50/60Hz	Flicker	Low flicker (less than 7%)
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 YEARS
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	45°		

CODING

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.	
8036		AR		3 =3000°K-CRI80		6 =6500°K-CRI80		GL =on/off	GI =vetro infrangibile
				4 =4000°K-CRI80		R =5700°K-CRI90		GD =dali	GA =vetro acidato
				5 =5000°K-CRI80				GM =1-10V	G1 =em. 1h

ACCESSORIES

Acc.068	Acc.069	Acc.070	Acc.071
Acc.088	Acc.089	Acc.030	

PERFORMANCE

W tot.	N°led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
80	2	150W JM/SAP	14505	10552	132	315	85	445	6,5
118	2	250W JM	19759	14374	122	315	85	445	6,5
130	2	250W JM/SAP	21403	15570	120	315	85	445	6,5
150	2	250W JM/SAP	25058	18221	121	315	85	445	6,5
170	2	400W JM	26666	19399	114	315	85	445	6,5
185	2	400W JM	29292	21309	115	315	85	445	6,5

The luminous flux and the total power absorbed by the system have a tolerance of ± 10% with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90= -13,73% lm

