



art. 8036 LORD 2/CR

Mod	CR	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder silver color, tempered transparent glass mm 5 thickness, silicon gasket	Optics	29° narrow beam matt satin aluminium reflector.
Insulation class	Class I	Protection index	IP66
Impact degree	IK08	Ambient temperature (Ta)	-25 / +45 °C
Power supply	220-240V 50/60Hz	Flicker	Low flicker (less than 7%)
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 YEARS
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	29°		

CODING

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.	
8036		CR		3	=3000°K-CRI80	6	=6500°K-CRI80	GL	=on/off
				4	=4000°K-CRI80	R	=5700°K-CRI90	GD	=dali
				5	=5000°K-CRI80			GM	=1-10V
									G1 =vetro infrangibile
									GA =vetro acidato
									G1 =em. 1h

ACCESSORIES

Acc.068	Acc.069	Acc.070	Acc.071
Acc.088	Acc.089	Acc.030	

PERFORMANCE

W tot.	N°led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
80	2	150W JM/SAP	14505	11032	138	315	85	445	6,5
118	2	250W JM	19759	15027	127	315	85	445	6,5
130	2	250W JM/SAP	21403	16278	125	315	85	445	6,5
150	2	250W JM/SAP	25058	19050	127	315	85	445	6,5
170	2	400W JM	26666	20280	119	315	85	445	6,5
185	2	400W JM	29292	22278	120	315	85	445	6,5

The luminous flux and the total power absorbed by the system have a tolerance of ± 10% with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90 = -13,73% lm

