



## art. 8036 LORD 2/PR

<b>Mod</b>	PR	<b>Installation</b>	Indoor and outdoor floodlight
<b>Material</b>	Die cast aluminium body, painted with polyester coated anticorrosion powder silver color, tempered transparent glass mm 5 thickness, silicon gasket	<b>Optics</b>	90° wide beam matt satin aluminium reflector.
<b>Insulation class</b>	Class I	<b>Protection index</b>	IP66
<b>Impact degree</b>	IK08	<b>Ambient temperature (Ta)</b>	-25 / +45 °C
<b>Power supply</b>	220-240V 50/60Hz	<b>Flicker</b>	Low flicker (less than 7%)
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1:2015	<b>Warranty</b>	7 YEARS
<b>Luminous flux maintenance</b>	L80-B20 (50.000h) - L80-B50 (75.000h)	<b>Photobiological safety class</b>	IEC 62471: Exempt group
<b>Beam angle</b>	90°		

### CODING

<b>Art.</b>	<b>+</b>	<b>Mod.</b>	<b>+</b>	<b>°K</b>	<b>+</b>	<b>W-tot.</b>	<b>+</b>	<b>Opt.</b>	
8036		PR		3	=3000°K-CRI80	6	=6500°K-CRI80	GL	=on/off
				4	=4000°K-CRI80	R	=5700°K-CRI90	GD	=dali
				5	=5000°K-CRI80			GM	=1-10V
									G1 =vetro infrangibile
									GA =vetro acidato
									G1 =em. 1h

### ACCESSORIES

Acc.068	Acc.069	Acc.070	Acc.071
Acc.088	Acc.089	Acc.030	

### PERFORMANCE

W tot.	N°led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
80	2	150W JM/SAP	14505	11635	145	315	85	445	6,5
118	2	250W JM	19759	15848	134	315	85	445	6,5
130	2	250W JM/SAP	21403	17168	132	315	85	445	6,5
150	2	250W JM/SAP	25058	20091	134	315	85	445	6,5
170	2	400W JM	26666	21389	126	315	85	445	6,5
185	2	400W JM	29292	23495	127	315	85	445	6,5

The luminous flux and the total power absorbed by the system have a tolerance of ± 10% with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90 = -13,73% lm

