



art. 8033 LORD 3/AR

Mod	AR	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder anthracite color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP66	Impact degree	IK08
Ambient temperature (Ta)	-25 / +45 °C	Optics	Matt satin asymmetric aluminium reflector 45°
Power supply	220-240V 50/60Hz	Flicker	Low flicker
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 Years
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	45°		

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
8033		AR		3 = 3000°K		130		GL = standard
				4 = 4000°K		150		GM = 1-10 V
				5 = 5000°K		200		GD = dali
				6 = 6500°K		230		GS = sanded glass
								GV = shatterproof glass

ACCESSORIES

AP8033GL - Pole bracket

GP8033 - Protection grid

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
130	4000	22411	16938	395	105	455	9,0	3 led	250W JM/SAP
150	4000	24880	18804	395	105	455	9,0	3 led	250W JM/SAP
200	4000	35331	26703	395	105	455	9,0	4 led	400W JM/SAP
230	4000	39530	29876	395	105	455	9,0	4 led	400W JM/SAP

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3,0% lm

