



art. 8032 LORD 4/PM

Mod	PM	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder silver color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP65	Impact degree	IK08
Color rendering index (CRI)	> 80	Ambient temperature (Ta)	-25 / +45 °C
Optics	Matt satin symmetric aluminium reflector.	Power supply	220-240V 50/60Hz
Flicker	Low flicker	Incandescent wire resistance	850°
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 Years
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	90°	RAL	9006

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
8032		PM		3 = 3000°K		150		GL = standard
				4 = 4000°K		175		GM = 1-10 V
				5 = 5000°K		200		GD = dali
				6 = 6500°K		230		G1 = em. 1h
						280		GS = sanded glass
						300		GV = shatterproof glass

ACCESSORIES

AP8032GL - Pole bracket

GP8032 - Protection grid

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
150	4000	28405	20127	395	155	455	9,1	4 led	250W SAP
175	4000	31898	22602	395	155	455	9,1	4 led	400W JM
200	4000	35331	25034	395	155	455	9,1	4 led	400W JM/SAP
230	4000	39530	28009	395	155	455	9,1	4 led	400W JM/SAP
280	4000	46005	32597	395	155	455	9,1	4 led	600W SAP
300	4000	48348	34257	395	155	455	9,1	4 led	600W SAP

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

