



## art. 8055 LORD 5/PM

<b>Mod</b>	PM	<b>Installation</b>	Indoor and outdoor floodlight
<b>Material</b>	Die cast aluminium body, painted with polyester coated anticorrosion powder anthracite color, tempered transparent glass mm 5 thickness, silicon gasket	<b>Insulation class</b>	Class I
<b>Protection index</b>	IP65	<b>Impact degree</b>	IK08
<b>Color rendering index</b>	> 80	<b>Ambient temperature (Ta)</b>	-25 / +45 °C
<b>Optics</b>	Matt satin symmetric aluminium reflector	<b>Power supply</b>	220-240V 50/60Hz
<b>Flicker</b>	Low flicker	<b>Incandescent wire resistance</b>	850°
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1:2015	<b>Warranty</b>	7 YEARS
<b>Luminous flux maintenance</b>	L80-B20 (50.000h) - L80-B50 (75.000h)	<b>Photobiological safety class</b>	IEC 62471: Exempt group
<b>Beam angle</b>	90°	<b>RAL</b>	9006

### CODE

<b>Art.</b>	+	<b>Mod.</b>	+	<b>°K</b>	+	<b>W-tot.</b>	+	<b>Opt.</b>
8055		GL		3 = 3000°K		315		GL = standard
				4 = 4000°K				GM = 1-10 V
				5 = 5000°K				GD = dali
				6 = 6500°K				GS = sanded glass
								GV = shatterproof glass

<b>W-tot</b>	<b>°K</b>	<b>Lm [Tc=25°]</b>	<b>Lm [Output]</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>Kg</b>	<b>Lamp</b>	<b>Sost.</b>
315	4000	52930	37489	535	165	255	205	10,0	4 led	?600W SAP

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

