



art. 8029 LORDINO/CR

Mod	CR	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder anthracite color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP66	Impact degree	IK08
Ambient temperature (Ta)	-25 / +45 °C	Optics	Matt satin narrow beam aluminium reflector
Power supply	220-240V 50/60Hz	Flicker	Low flicker
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 Years
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	30°		

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
8029		CR		30 = 3000°K		20		EL = standard
				40 = 4000°K		30		LM = 1-10 V
				50 = 5000°K		40		LD = dali
				65 = 6500°K		50		VS = sanded glass
						68		VI = Shatterproof glass

ACCESSORI

AP8029EL - Pole bracket

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
20	4000	3214	2475	180	65	330	2,0	1 led	300W halog.
30	4000	4518	3479	180	65	330	2,0	1 led	70W JM
40	4000	5827	4486	180	65	330	2,0	1 led	70W SAP
50	4000	7102	5452	180	65	330	2,0	1 led	100W JM/SAP
68	4000	9845	7579	180	65	330	2,0	1 led	150W JM

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

