



art. 8029 LORDINO/PM

Mod	PM	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder silver color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP65	Impact degree	IK08
Color rendering index (CRI)	> 80	Ambient temperature (Ta)	-25 / +45 °C
Optics	Matt satin narrow beam aluminium reflector	Power supply	230V 50/60Hz
Incandescent wire resistance	850°	Trademarks and certifications	CE / UNI EN 60598-1:2015
Warranty	5 Years	Luminous flux maintenance	L80-B50 (75.000h) - L70-B50 (130.000h)
Photobiological safety class	IEC 62471: Exempt group	Beam angle	90°

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
8029		PM		30 = 3000°K		20		GL = standard
				40 = 4000°K		30		GM = 1-10 V
				50 = 5000°K		40		GD = dali
						50		GV = shatterproof glass
						65		

ACCESSORIES

AP8029GL - Pole bracket

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
20	4000	3214	2277	275	155	65	2,0	1 led HP	300W halog.
30	4000	4518	3201	275	155	65	2,0	1 led HP	70W JM
40	4000	5827	4128	275	155	65	2,0	1 led HP	70W SAP
50	4000	7081	5017	275	155	65	2,0	1 led HP	500W halog.
65	4000	8153	5777	275	155	65	2,0	1 led HP	125W merc.

*The flux may vary from -5/+5% compared to the real

- 3000K = -5,28% lm • 4000K = standard • 5000K = +0,90% lm

