



## art. 8029 LORDINO/RR

<b>Mod</b>	RR	<b>Installation</b>	Indoor and outdoor floodlight
<b>Material</b>	Die cast aluminium body, painted with polyester coated anticorrosion powder anthracite color, tempered transparent glass mm 5 thickness, silicon gasket	<b>Insulation class</b>	Class I
<b>Protection index</b>	IP66	<b>Impact degree</b>	IK08
<b>Ambient temperature (Ta)</b>	-25 / +45 °C	<b>Optics</b>	Matt satin asymmetric aluminium reflector
<b>Power supply</b>	220-240V 50/60Hz	<b>Flicker</b>	Low flicker
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1:2015	<b>Warranty</b>	7 Years
<b>Luminous flux maintenance</b>	L80-B20 (50.000h) - L80-B50 (75.000h)	<b>Photobiological safety class</b>	IEC 62471: Exempt group
<b>Beam angle</b>	55°		

### CODE

<b>Art.</b>	+	<b>Mod.</b>	+	<b>°K</b>	+	<b>W-tot.</b>	+	<b>Opt.</b>
8029		AR		30 = 3000°K		20		EL = standard
				40 = 4000°K		30		LM = 1-10 V
				50 = 5000°K		40		LD = dali
				65 = 6500°K		50		VS = sanded glass
						68		VI = Shatterproof glass

### ACCESSORIES

AP8029EL - Pole bracket

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
20	4000	3214	2308	180	65	330	2,0	1 led	300W halog.
30	4000	4518	3244	180	65	330	2,0	1 led	70W JM
40	4000	5827	4183	180	65	330	2,0	1 led	70W SAP
50	4000	7102	5084	180	65	330	2,0	1 led	100W JM/SAP
68	4000	9845	7068	180	65	330	2,0	1 led	150W JM

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

