



art. 8057 MEGA-LORD/CR

Mod	CR	Installation	Indoor and outdoor floodlight
Material	Silver extruded aluminium oxydate body, zinc-coated bracket, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP65	Impact degree	IK08
Ambient temperature (Ta)	-25 / +45 °C	Optics	Matt satin symmetric aluminium reflector
Power supply	220-240V 50/60Hz	Flicker	Low flicker
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 YEARS
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	29°		

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
8057		CR		3 = 3000°K		600		GR = standard
				4 = 4000°K		900		GL = driver on-board (28 Kg)
				5 = 5000°K				GM = 1-10 V
				6 = 6500°K				GD = dali
								GS = sanded glass
								GI = shatterproof glass

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	D	Kg	Lamp	Sost.
600	4000	105993	81612	720	105	455	400	21,0	12 led	1000W JM/SAP
900	4000	153562	118191	720	105	455	400	25,0	12 led	2000W JM
BOX	A	B	C	Kg						
	470	210	200	8,0						

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

