



series **prince**

made in Italy

TECHNICAL DATA

OPTIONS

General information	Power supply:	220-240V - 50/60Hz
	Protection index:	IP65
	Power factor:	0,97 (cos phi)
	Ballast:	Electronic ballast
Material body:	Trafilated aluminium oxidate	
	Glass:	Temperated transparent glass. Thickness 5mm
	Installation:	Bracket installation
Operating temperature:	-30+45°C	
LED	Tecnology:	LED Lighting
	CRI (Ra):	>80
	Life time estimated (h):	>50.000 h
	Degradation index:	(L70 = 130.000h) (L80 = 75.000h)
	Lm/W:	160
Optics	Light diffusion:	Direct light
	Optics type:	PR - Symmetric floodlight
Norms	Optics angle:	90°
	Norms:	EN / IEC 60598-1:2015
	Eyesafety (IEC 62471):	Risk group exempt

	VI8097 Shatterproof glass
	IM8097 Dimmerable 1-10V electronic ballast
	LD8097 Dimmerabile Dali Driver ballast for LED
<b>3000K</b>	3K8097 LED color 3000K

MOD.	W	Cod. EL	lamp	°K	Lm (Tc=25°)	Lm (Output)	A	B	C	Kg	mc		
PR	480	8097PR4480EL	8 led HP	4000	76288	61104	635	280	150	14,5	0,040	1	30
	480	8097PR5480EL	8 led HP	5000	77056	61818	635	280	150	14,5	0,040	1	30

\*The flux may vary from -5/+5% compared to the real.