



## art. 8035 MINI-LORD/CR

<b>Mod</b>	CR	<b>Installation</b>	Indoor and outdoor floodlight
<b>Material</b>	Die cast aluminium body, painted with polyester coated anticorrosion powder silver color, tempered transparent glass mm 5 thickness, silicon gasket	<b>Insulation class</b>	Class I
<b>Protection index</b>	IP66	<b>Impact degree</b>	IK08
<b>Color rendering index (CRI)</b>	> 80	<b>Ambient temperature (Ta)</b>	-25 / +45 °C
<b>Optics</b>	Matt satin symmetric aluminium reflector	<b>Power supply</b>	220-240V 50/60Hz
<b>Flicker</b>	Low flicker	<b>Incandescent wire resistance</b>	850°
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1:2015	<b>Warranty</b>	7 YEARS
<b>Luminous flux maintenance</b>	L80-B20 (50.000h) - L80-B50 (75.000h)	<b>Photobiological safety class</b>	IEC 62471: Exempt group
<b>Beam angle</b>	30°	<b>RAL</b>	9006

### CODE

<b>Art.</b>	+	<b>Mod.</b>	+	<b>°K</b>	+	<b>W-tot.</b>	+	<b>Opt.</b>
8035		CR		3 = 3000°K		118		GL = standard
				4 = 4000°K		148		GM = 1-10 V
				5 = 5000°K		178		GD = dali
				6 = 6500°K				G1 = em.1h
								GS = sanded glass
								GI = shatterproof glass

### ACCESSORIES

AP8035GL - Pole bracket

GP8035 - Protection grid

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
118	4000	18682	14385	315	85	445	6,5	2 led	250W JM
148	4000	24174	18613	315	85	445	6,5	2 led	250W JM/SAP
178	4000	27534	21201	315	85	45	6,5	2 led	400W JM

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

