



art. 8035 MINI-LORD/PM

Mod	PM	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder silver color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP66	Impact degree	IK08
Color rendering index (CRI)	> 80	Ambient temperature (Ta)	-25 / +45 °C
Optics	Matt satin symmetric aluminium reflector	Power supply	220-240V 50/60Hz
Flicker	Low flicker	Incandescent wire resistance	850°
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 Years
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	90°	RAL	9006

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
8035		PM		3 = 3000°K		118		GL = standard
				4 = 4000°K		148		GM = 1-10 V
				5 = 5000°K		178		GD = dali
				6 = 6500°K				G1 = em.1h
								GS =sanded glass
								GI = shatterproof glass

ACCESSORIES

AP8035GL - Pole bracket

GP8035 - Protection grid

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
118	4000	18682	13238	315	85	445	6,5	2 led	250W JM
148	4000	24174	17129	315	85	445	6,5	2 led	250W JM/SAP
178	4000	27534	19510	315	85	445	6,5	2 led	400W JM

The luminous flux and the system total absorbed power have a tolerance of ± 10% of the given values.

- 3000K = -5,28% lm
- 4000K = standard
- 5000K = +0,90% lm
- 6500K = +3.0% lm

