


Download LDT file from www.tec-mar.it



series **prince**

made in Italy

TECHNICAL DATA

General information	Power supply:	220-240V - 50/60Hz
	Protection index:	IP65
	Power factor:	0,97 (cos phi)
	Ballast:	Electronic ballast
	Material body:	Trafilated aluminium oxidate
LED	Glass:	Temperated transparent glass. Thickness 5mm
	Installation:	Bracket installation
	Operating temperature:	-30+45°C
	Technology:	LED Lighting
	CRI (Ra):	>80
Optics	Life time estimated (h):	>50.000 h
	Degradation index:	(L70 = 1.30.000h) (L80 = 75.000h)
	Lm/W:	160
	Light diffusion:	Direct light
	Optics type:	AR - Asymmetric floodlight
Norms	Optics angle:	45°
	Norms:	EN / IEC 60598-1:2015
	Eyesafety (IEC 62471):	Risk group exempt

OPTIONS

	VI8094 Shatterproof glass
	AP8094 Pole bracket
	IM8094 Dimmerable 1-10V electronic ballast
	LD8094 Dimmerable Dali Driver ballast for LED
3000K	3K8094 LED color 3000K

MOD.	W	Cod. EL	lamp	°K	Lm (Tc=25°)	Lm (Output)	A	B	C	Kg	mc		
AR	55	8094AR4055EL	1 led HP	4000	8480	6393	315	280	150	6,5	0,022	1	50
	55	8094AR5055EL	1 led HP	5000	8566	6468	315	280	150	6,5	0,022	1	50
	80	8094AR4080EL	1 led HP	4000	12368	9323	315	280	150	6,5	0,022	1	50
	80	8094AR5080EL	1 led HP	5000	12492	9432	315	280	150	6,5	0,022	1	50
	120	8094AR4120EL	1 led HP	4000	16891	12733	315	280	150	6,5	0,022	1	50
	120	8094AR5120EL	1 led HP	5000	17061	12883	315	280	150	6,5	0,022	1	50
	150	8094AR4150EL	1 led HP	4000	23751	17904	315	280	150	6,5	0,022	1	50
	150	8094AR5150EL	1 led HP	5000	23992	18115	315	280	150	6,5	0,022	1	50

*The flux may vary from -5/+5% compared to the real.