


Download LDT file from www.tec-mar.it



series **prince**

made in Italy

TECHNICAL DATA

General information	Power supply:	220-240V - 50/60Hz
	Protection index:	IP65
	Power factor:	0,97 (cos phi)
	Ballast:	Electronic ballast
	Material body:	Trafilated aluminium oxidate
LED	Glass:	Temperated transparent glass. Thickness 5mm
	Installation:	Suspending installation
	Operating temperature:	-30+45°C
	Tecnology:	LED Lighting
	CRI (Ra):	>80
Optics	Life time estimated (h):	>50.000 h
	Degradation index:	(L70 = 130.000h) (L80 = 75.000h)
	Lm/W:	160
Norms	Light diffusion:	Direct light
	Optics type:	SU - Symmetric High-Bay
	Optics angle:	90°
	Norms:	EN / IEC 60598-1:2015
	Eyesafety (IEC 62471):	Risk group exempt

OPTIONS

	VI8094 Shatterproof glass
	IM8094 Dimmerable 1-10V electronic ballast
	LD8094 Dimmerabile Dali Driver ballast
	IN8094 Frame for recessed.
	PL8094 Kit surface moutage.
3000K	3K8094 LED color 3000K

MOD.	W	Cod. EL	lamp	°K	Lm (Tc=25°)	Lm (Output)	A	B	C	Kg	mc		
SU	55	8094SU4055EL	1 led HP	4000	8480	6793	315	280	230	6,5	0,022	1	50
	55	8094SU5055EL	1 led HP	5000	8566	6872	315	280	230	6,5	0,022	1	50
	80	8094SU4080EL	1 led HP	4000	12368	9905	315	280	230	6,5	0,022	1	50
	80	8094SU5080EL	1 led HP	5000	12492	10022	315	280	230	6,5	0,022	1	50
	120	8094SU4120EL	1 led HP	4000	16891	13529	315	280	230	6,5	0,022	1	50
	120	8094SU5120EL	1 led HP	5000	17061	13688	315	280	230	6,5	0,022	1	50
	150	8094SU4150EL	1 led HP	4000	23751	19023	315	280	230	6,5	0,022	1	50
	150	8094SU5150EL	1 led HP	5000	23992	19247	315	280	230	6,5	0,022	1	50

*The flux may vary from -5/+5% compared to the real.