



art. 8054.LORD 5 HP/CR

Mod	CR	Insulation class	Class I
Material	Silver oxidized drawn aluminum body, galvanized bracket, transparent tempered glass, silicone gasket.	Optics	29° narrow beam matt satin aluminium reflector.
Installation	Indoor and outdoor floodlight suitable for lighting large areas and sports facilities.	Protection index	IP65
Impact degree	IK08	Ambient temperature (Ta)	-25 / +45 °C
Power supply	220-240Vac 50/60Hz	Flicker	low flicker (less than 7%)
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 YEARS
Luminous flux maintenance	L80-B20 (50.000h)-L80-B50 (75.000h)	Photobiological safety class	risk group: Exempt
Beam angle	29°		

CODING

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.		
8054		CR		3	=3000°K-CRI70	6	=6500°K-CRI70	GL	=on/off	GV =vetro infrangibile
				4	=4000°K-CRI70	R	=5700°K-CRI90	GD	=dali	GA =vetro acidato
				5	=5000°K-CRI70			GM	=1-10V	

ACCESSORIES

Acc.093

PERFORMANCE

W tot.	N°led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
500	4+4	1000W SAP	86419	70431	141	600	315	455	22,2
600	4+4	1000W SAP	100231	81688	136	600	315	455	22,2

The luminous flux and the total power absorbed by the system have a tolerance of ± 10% with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90= -13,73% lm

