



art. 8054.LORD 5 HP/MR

| | | | |
|--------------------------------------|---|-------------------------------------|--|
| Mod | MR | Insulation class | Class I |
| Material | Silver oxidized drawn aluminum body, galvanized bracket, transparent tempered glass, silicone gasket. | Optics | 70° wide beam matt satin aluminium reflector |
| Installation | Indoor and outdoor floodlight suitable for lighting large areas and sports facilities. | Protection index | IP65 |
| Impact degree | IK08 | Ambient temperature (Ta) | -25 / +45 °C |
| Power supply | 220-240Vac 50/60Hz | Flicker | low flicker (less than 7%) |
| Trademarks and certifications | CE / UNI EN 60598-1:2015 | Warranty | 7 YEARS |
| Luminous flux maintenance | L80-B20 (50.000h)-L80-B50 (75.000h) | Photobiological safety class | risk group: Exempt |
| Beam angle | 70° | | |

CODING

| | | | | | | | | | | |
|-------------|---|-------------|---|-----------|---------------|---------------|---------------|-------------|---------|------------------------|
| Art. | + | Mod. | + | °K | + | W-tot. | + | Opt. | | |
| 8054 | | MR | | 3 | =3000°K-CRI70 | 6 | =6500°K-CRI70 | GL | =on/off | GV =vetro infrangibile |
| | | | | 4 | =4000°K-CRI70 | R | =5700°K-CRI90 | GD | =dali | GA =vetro acidato |
| | | | | 5 | =5000°K-CRI70 | | | GM | =1-10V | |

ACCESSORIES

Acc.093

PERFORMANCE

| W tot. | N°led | REPLACE | LUMEN LED | LUMEN OUTPUT | Lm/W | A(mm) | B(mm) | C(mm) | Kg |
|--------|-------|-----------|-----------|--------------|------|-------|-------|-------|------|
| 500 | 4+4 | 1000W SAP | 86419 | 67406 | 135 | 600 | 315 | 455 | 22,2 |
| 600 | 4+4 | 1000W SAP | 100231 | 78180 | 130 | 600 | 315 | 455 | 22,2 |

The luminous flux and the total power absorbed by the system have a tolerance of ± 10% with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90= -13,73% lm

