



## art. 8054.LORD 5 HP/RR

<b>Mod</b>	RR	<b>Insulation class</b>	Class I
<b>Material</b>	Silver oxidized drawn aluminum body, galvanized bracket, transparent tempered glass, silicone gasket.	<b>Optics</b>	65° asymmetric beam matt satin aluminium reflector.
<b>Installation</b>	Indoor and outdoor floodlight suitable for lighting large areas and sports facilities.	<b>Protection index</b>	IP65
<b>Impact degree</b>	IK08	<b>Ambient temperature (Ta)</b>	-25 / +45 °C
<b>Power supply</b>	220-240Vac 50/60Hz	<b>Flicker</b>	low flicker (less than 7%)
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1:2015	<b>Warranty</b>	7 YEARS
<b>Luminous flux maintenance</b>	L80-B20 (50.000h)-L80-B50 (75.000h)	<b>Photobiological safety class</b>	risk group: Exempt
<b>Beam angle</b>	65°		

### CODING

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.				
8054		RR		3	=3000°K-CRI70	6	=6500°K-CRI70	500	GL	=on/off	GV	=vetro infrangibile
				4	=4000°K-CRI70	R	=5700°K-CRI90	600	GD	=dali	GA	=vetro acidato
				5	=5000°K-CRI70				GM	=1-10V		

### ACCESSORIES

Acc.093

### PERFORMANCE

W tot.	N°led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
500	4+4	1000W SAP	86419	66542	133	600	315	455	22,2
600	4+4	1000W SAP	100231	77177	129	600	315	455	22,2

The luminous flux and the total power absorbed by the system have a tolerance of ± 10% with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90 = -13,73% lm

